



# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878  
Revision date: 23/02/2022 Supersedes: 25/02/2020 Version: 5.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

|                 |                             |
|-----------------|-----------------------------|
| Product form    | : Mixture                   |
| Trade name      | : Eni Multitech JD/F 10W-30 |
| Product code    | : 1281                      |
| Type of product | : Lubricants                |
| Formula         | : 0285-2021                 |
| Product group   | : Trade product             |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

|                                  |   |
|----------------------------------|---|
| Main use category                | : Industrial use, Professional use, Consumer use  |
| Industrial/Professional use spec | : Wide dispersive use   |
| Use of the substance/mixture     | : Gearbox lubricant<br>-----<br>Do not use the product for any purposes that have not been advised by the manufacturer. |
| Function or use category         | : Lubricants and additives  |

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

ENI S.p.A.  
P.le E. Mattei 1 - 00144 Rome Italy  
Phone: (+39) 06 59821  
www.eni.com

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

#### 1.4. Emergency telephone number

|                  |  |
|------------------|--|
| Emergency number | : CNIT +39 0382 24444 (24h) (IT + EN)  |
|                  | Poison centre (UK):<br>National Poisons Information Service Edinburgh (24h)<br>(+44) 844 892 0111<br>0870 600 6266 (UK only)<br>(Source: UN-WHO) |

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Harmful to aquatic life with long lasting effects. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word : [None]

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                                |  |
|--------------------------------|--|
| Hazard statements (CLP)        | : H412 - Harmful to aquatic life with long lasting effects.  |
| Precautionary statements (CLP) | : P102 - Keep out of reach of children.<br>P273 - Avoid release to the environment.<br>P501 - Dispose of contents and container to according to national or local regulations. |
| EUH-statements                 | : EUH208 - Contains 2-tetradecyloxirane, reaction products with boric acid, Triphenyl phosphite. May produce an allergic reaction.   |

### 2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to a hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

| Component  |  |
|--|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)    | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Mineral base oil, severely refined (N/A)                               | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)       | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII  |

| Component   |   |
|---|---|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic(64742-65-0) | The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic(64742-65-0) | The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|  |   |
|--|---|
| Distillates (petroleum), hydrotreated light naphthenic(64742-53-6) | The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 |
| Mineral base oil, severely refined(N/A)                            | The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)(4259-15-8)    | The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 |

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Notes : Composition/ Information on ingredients:  
Mixture of hydrocarbons  
Additives

| Name  | Product identifier   | %         | Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP] |
|---|--|-----------|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic<br>(see note [**], see note [***], see note [****])   | (CAS-No.) 64742-65-0<br>(EC-No.) 265-169-7<br>(EC Index-No.) 649-474-00-6<br>(REACH-no) 01-2119471299-27 | 80 - 85   | Not classified   |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]<br>(see note [**], see note [****]) | (CAS-No.) 64742-65-0<br>(EC-No.) 265-169-7<br>(EC Index-No.) 649-474-00-6<br>(REACH-no) 01-2119471299-27 | 5 - 10    | Not classified   |
| Distillates (petroleum), hydrotreated light naphthenic<br>(see note [**], see note [****])  | (CAS-No.) 64742-53-6<br>(EC-No.) 265-156-6<br>(EC Index-No.) 649-466-00-2<br>(REACH-no) 01-2119480375-34 | 1 - 5     | Asp. Tox. 1, H304  |
| Mineral base oil, severely refined<br>(see note [*], see note [****])   | (CAS-No.) N/A<br>(EC-No.) N/A  | 1,2 – 3   | Asp. Tox. 1, H304  |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)<br>(Additive)  | (CAS-No.) 4259-15-8<br>(EC-No.) 224-235-5<br>(EC Index-No.) N/A<br>(REACH-no) 01-2119493635-27           | 1 -1,5    | Eye Dam. 1, H318<br>Aquatic Chronic 2, H411                              |
| 2-tetradecyloxirane, reaction products with boric acid<br>(Additive)  | (EC-No.) 701-392-2<br>(REACH-no) 01-2119976364-28  | 0,3 – 0,6 | Skin Sens. 1B, H317  |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                                   |  |             |  |
|-----------------------------------|--|-------------|--|
| Triphenyl phosphite<br>(Additive) | (CAS-No.) 101-02-0<br>(EC-No.) 202-908-4<br>(EC Index-No.) 015-105-00-7<br>(REACH-no) 01-2119511213-58 | 0,06 – 0,15 | Acute Tox. 4 (Oral), H302<br>(ATE=500 mg/kg bodyweight)<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| toluene                           | (CAS-No.) 108-88-3<br>(EC-No.) 203-625-9<br>(EC Index-No.) 601-021-00-3                                | 0,1 - 0,15  | Flam. Liq. 2, H225<br>Repr. 2, H361d<br>Asp. Tox. 1, H304<br>STOT RE 2, H373<br>Skin Irrit. 2, H315<br>STOT SE 3, H336   |

### Specific concentration limits:

| Name   | Product identifier   | Specific concentration limits   |
|--|--|---|
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)<br>(Additive) | (CAS-No.) 4259-15-8<br>(EC-No.) 224-235-5<br>(EC Index-No.) N/A<br>(REACH-no) 01-2119493635-27         | ( 50 ≤C < 100) Eye Dam. 1, H318                                       |
| Triphenyl phosphite<br>(Additive)                                  | (CAS-No.) 101-02-0<br>(EC-No.) 202-908-4<br>(EC Index-No.) 015-105-00-7<br>(REACH-no) 01-2119511213-58 | ( 5 ≤C < 100) Skin Irrit. 2, H315<br>( 5 ≤C < 100) Eye Irrit. 2, H319 |

Notes : [\*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):  
CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx.  
All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)  
Note [\*\*]:  
this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.  
Note [\*\*\*]:  
substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)  
Note [\*\*\*\*]:  
this product may be formulated with one or more of the following base oils (not classified as hazardous):CAS 64742-54-7/ REACH Reg. # 01-2119484627-25-XXXX; CAS 64742-65-0/ REACH Reg. # 01-2119471299-27-XXXX; CAS 101316-72-7/EC 309-877-7/ REACH Reg. # 01-2119489969-06-XXXX; CAS 64742-65-0/ EC 265-169-7/ REACH Reg # 01-2119471299-27-XXXX/ EC index No 649-474-00-6

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

First-aid measures after skin contact : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Do not put ice on the burn.

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                                      |   |
|--------------------------------------|---|
| First-aid measures after eye contact | : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. |
| First-aid measures after ingestion   | : Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.                 |

### 4.2. Most important symptoms and effects, both acute and delayed

|  |   |
|--|---|
| Symptoms/effects after inhalation                | : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness. |
| Symptoms/effects after skin contact              | : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Contact with hot product may cause thermal burns.   |
| Symptoms/effects after eye contact               | : Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.  |
| Symptoms/effects after ingestion                 | : Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.  |
| Symptoms/effects upon intravenous administration | : No information available.   |
| Chronic symptoms                                 | : None to be reported, according to the present classification criteria.  |

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H<sub>2</sub>S (hydrogen sulphide). Send the casualty immediately to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations). |
| Unsuitable extinguishing media | : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.  |

### 5.2. Special hazards arising from the substance or mixture

|  |   |
|--|---|
| Fire hazard                                      | : This product is combustible, but not classed as flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels."  |
| Explosion hazard                                 | : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m <sup>3</sup> of air.  |
| Hazardous decomposition products in case of fire | : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NO <sub>x</sub> , H <sub>2</sub> S and SO <sub>x</sub> (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). PO <sub>x</sub> . ZnO <sub>x</sub> . BO <sub>x</sub> . |

### 5.3. Advice for firefighters

|   |  |
|---|--|
| Firefighting instructions                     | : Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area. |
| Special protective equipment for firefighters | : Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.       |
| Other information                             | : In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.   |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.

##### 6.1.1. For non-emergency personnel

Protective equipment : See Section 8.  
Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

##### 6.1.2. For emergency responders

Protective equipment : Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. If necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.  
Emergency procedures : Notify local authorities according to relevant regulations.

#### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.  
Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
- Hygiene measures : Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Take off immediately all contaminated clothing and wash it before reuse. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
- Incompatible products : Keep away from: strong oxidants.
- Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
- Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
- Packaging materials : For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

| Distillates (petroleum), hydrotreated light naphthenic (64742-53-6) |   |
|---|---|
| Austria - Occupational Exposure Limits                              |   |
| MAK (OEL TWA)   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Belgium - Occupational Exposure Limits                              |   |
| OEL TWA   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark - Occupational Exposure Limits                              |   |
| OEL TWA [1]   | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| <b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b> |  |
|--|--|
| OEL STEL   | 2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Hungary - Occupational Exposure Limits</b>                              |  |
| AK (OEL TWA)   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Netherlands - Occupational Exposure Limits</b>                          |  |
| MAC TGG 8h (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Spain - Occupational Exposure Limits</b>                                |  |
| VLA-ED (OEL TWA) [1]   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| VLA-EC (mg/m <sup>3</sup> )  | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>Sweden - Occupational Exposure Limits</b>                               |  |
| NGV (OEL TWA)  | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| KTV (OEL STEL)   | 3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>United Kingdom - Occupational Exposure Limits</b>                       |  |
| WEL TWA (OEL TWA) [1]  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| WEL STEL (OEL STEL)  | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                          |  |
| ACGIH OEL TWA  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| ACGIH OEL STEL   | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

| <b>toluene (108-88-3)</b>                                 |         |
|---|---------|
| <b>EU - Indicative Occupational Exposure Limit (IOEL)</b> |         |
| IOELV TWA (ppm)   | 50 ppm  |
| IOELV STEL (ppm)  | 100 ppm |
| <b>Austria - Occupational Exposure Limits</b>             |         |
| MAK [ppm]   | 50 ppm  |
| MAK Short time value [ppm]                                | 100 ppm |
| <b>Belgium - Occupational Exposure Limits</b>             |         |
| Limit value [ppm]   | 20 ppm  |
| Short time value [ppm]                                    | 100 ppm |
| <b>Denmark - Occupational Exposure Limits</b>             |         |
| OEL TWA [2]   | 25 ppm  |
| Grænseværdi (kortvarig) (ppm)                             | 50 ppm  |
| <b>Finland - Occupational Exposure Limits</b>             |         |
| HTP (OEL TWA) [2]   | 25 ppm  |
| HTP-arvo (15 min) (ppm)                                   | 100 ppm |
| <b>France - Occupational Exposure Limits</b>              |         |
| VME [ppm]   | 100 ppm |
| VLE [ppm]   | 20 ppm  |
| <b>Germany - Occupational Exposure Limits (TRGS 900)</b>  |         |
| AGW (OEL TWA) [2]   | 50 ppm  |
| Limitation of exposure peaks (ppm)                        | 200 ppm |



# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| <b>toluene (108-88-3)</b>   |   |
|---|---|
| <b>Hungary - Occupational Exposure Limits</b>                                 |   |
| CK-érték  | 190 mg/m <sup>3</sup>   |
| MK-érték  | 380 mg/m <sup>3</sup>   |
| <b>Ireland - Occupational Exposure Limits</b>                                 |   |
| OEL TWA [2]   | 50 ppm  |
| OEL (15 min ref) (ppm)  | 100 ppm   |
| <b>Italy - Occupational Exposure Limits</b>                                   |   |
| OEL TWA (mg/m <sup>3</sup> )  | 192 mg/m <sup>3</sup>   |
| OEL TWA (ppm)   | 50 ppm  |
| <b>Latvia - Occupational Exposure Limits</b>                                  |   |
| OEL TWA (ppm)   | 14 ppm  |
| OEL STEL [ppm]  | 40 ppm  |
| <b>Netherlands - Occupational Exposure Limits</b>                             |   |
| MAC TGG 8h (mg/m <sup>3</sup> )   | 150 mg/m <sup>3</sup>   |
| MAC TGG 15 min (mg/m <sup>3</sup> )   | 384 mg/m <sup>3</sup>   |
| <b>Poland - Occupational Exposure Limits</b>                                  |   |
| NDS (OEL TWA)   | 100 mg/m <sup>3</sup>   |
| NDSP (mg/m <sup>3</sup> )   | 200 mg/m <sup>3</sup>   |
| <b>Spain - Occupational Exposure Limits</b>                                   |   |
| VLA-ED (OEL TWA) [2]  | 50 ppm  |
| VLA-EC (ppm)  | 100 ppm   |
| <b>Sweden - Occupational Exposure Limits</b>                                  |   |
| Nivågränsvärde (NVG) (ppm)  | 50 ppm  |
| KTV (OEL STEL) [ppm]  | 100 ppm   |
| <b>United Kingdom - Occupational Exposure Limits</b>                          |   |
| WEL TWA (OEL TWA) [2]   | 50 ppm  |
| WEL STEL (OEL STEL) [ppm]   | 100 ppm   |
| <b>Switzerland - Occupational Exposure Limits</b>                             |   |
| MAK (OEL TWA) [1]   | 190 mg/m <sup>3</sup>   |
| MAK (OEL TWA) [2]   | 50 ppm  |
| VLE [mg/m <sup>3</sup> ]  | 760 mg/m <sup>3</sup>   |
| VLE [ppm]   | 200 ppm   |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                             |   |
| ACGIH TLV®-TWA (ppm)  | 50 ppm  |
| <b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b> |   |
| <b>Austria - Occupational Exposure Limits</b>                                 |   |
| MAK (OEL TWA)   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>Belgium - Occupational Exposure Limits</b>                                 |   |
| OEL TWA   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

| <b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b> |  |
|---|--|
| <b>Denmark - Occupational Exposure Limits</b>                                 |  |
| OEL TWA [1]   | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| OEL STEL  | 2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Hungary - Occupational Exposure Limits</b>                                 |  |
| AK (OEL TWA)  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Netherlands - Occupational Exposure Limits</b>                             |  |
| MAC TGG 8h (mg/m <sup>3</sup> )   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Spain - Occupational Exposure Limits</b>                                   |  |
| VLA-ED (OEL TWA) [1]  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| VLA-EC (mg/m <sup>3</sup> )   | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>Sweden - Occupational Exposure Limits</b>                                  |  |
| NGV (OEL TWA)   | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| KTV (OEL STEL)  | 3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>United Kingdom - Occupational Exposure Limits</b>                          |  |
| WEL TWA (OEL TWA) [1]   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| WEL STEL (OEL STEL)   | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                             |  |
| ACGIH OEL TWA   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| ACGIH OEL STEL  | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

|   |  |
|---|--|
| <b>Austria - Occupational Exposure Limits</b>     |  |
| MAK (OEL TWA)                                     | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Belgium - Occupational Exposure Limits</b>     |  |
| OEL TWA   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Denmark - Occupational Exposure Limits</b>     |  |
| OEL TWA [1]                                       | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| OEL STEL  | 2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Hungary - Occupational Exposure Limits</b>     |  |
| AK (OEL TWA)                                      | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Netherlands - Occupational Exposure Limits</b> |  |
| MAC TGG 8h (mg/m <sup>3</sup> )                   | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| <b>Spain - Occupational Exposure Limits</b>       |  |
| VLA-ED (OEL TWA) [1]                              | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| VLA-EC (mg/m <sup>3</sup> )                       | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| <b>Sweden - Occupational Exposure Limits</b>      |  |
| NGV (OEL TWA)                                     | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| KTV (OEL STEL)                                    | 3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

### United Kingdom - Occupational Exposure Limits

|                       |  |
|-----------------------|--|
| WEL TWA (OEL TWA) [1] | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| WEL STEL (OEL STEL)   | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

### USA - ACGIH - Occupational Exposure Limits

|                |  |
|----------------|--|
| ACGIH OEL TWA  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| ACGIH OEL STEL | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

### Mineral base oil, severely refined (N/A)

#### Austria - Occupational Exposure Limits

|               |   |
|---------------|---|
| MAK (OEL TWA) | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
|---------------|---|

#### Belgium - Occupational Exposure Limits

|         |   |
|---------|---|
| OEL TWA | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
|---------|---|

#### Denmark - Occupational Exposure Limits

|             |   |
|-------------|---|
| OEL TWA [1] | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| OEL STEL    | 2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

#### Hungary - Occupational Exposure Limits

|              |   |
|--------------|---|
| AK (OEL TWA) | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
|--------------|---|

#### Netherlands - Occupational Exposure Limits

|                                 |   |
|---------------------------------|---|
| MAC TGG 8h (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
|---------------------------------|---|

#### Spain - Occupational Exposure Limits

|                             |  |
|-----------------------------|--|
| VLA-ED (OEL TWA) [1]        | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| VLA-EC (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

#### Sweden - Occupational Exposure Limits

|                |   |
|----------------|---|
| NGV (OEL TWA)  | 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| KTV (OEL STEL) | 3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

### United Kingdom - Occupational Exposure Limits

|                       |  |
|-----------------------|--|
| WEL TWA (OEL TWA) [1] | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| WEL STEL (OEL STEL)   | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

### USA - ACGIH - Occupational Exposure Limits

|                |  |
|----------------|--|
| ACGIH OEL TWA  | 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)  |
| ACGIH OEL STEL | 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

### 8.1.2. Recommended monitoring procedures

#### Monitoring methods

|                    |  |
|--------------------|--|
| Monitoring methods | Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene. |
|--------------------|--|

### 8.1.3. Air contaminants formed

No additional information available

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.1.4. DNEL and PNEC

| Eni Multitech JD/F 10W-30                 |                |
|---|----------------|
| <b>DNEL/DMEL (additional information)</b> |                |
| Additional information                    | Not applicable |
| <b>PNEC (additional information)</b>      |                |
| Additional information                    | Not applicable |

| Distillates (petroleum), hydrotreated light naphthenic (64742-53-6) |                           |
|---|---------------------------|
| <b>DNEL/DMEL (Workers)</b>  |                           |
| Long-term - systemic effects, dermal                                | 0,97 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation                            | 2,73 mg/m <sup>3</sup>    |
| Long-term - local effects, inhalation                               | 5,58 mg/m <sup>3</sup>    |
| <b>DNEL/DMEL (General population)</b>                               |                           |
| Long-term - systemic effects, oral                                  | 0,74 mg/kg bodyweight/day |
| Long-term - local effects, inhalation                               | 1,19 mg/m <sup>3</sup>    |

Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure that there is a suitable ventilation system. Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

### 8.2.2. Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

#### 8.2.2.2. Skin protection

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

### Hand protection:

When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H<sub>2</sub>S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Consumer exposure controls:

Ensure adequate ventilation. Avoid excessive or improper use. Wear protective gloves.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                             |  |
|-----------------------------|--|
| Physical state              | : Liquid   |
| Colour                      | : Yellow-brown.  |
| Appearance                  | : Liquid, bright & clear.  |
| Odour                       | : Slight odour of petroleum.                                     |
| Odour threshold             | : There are no data available on the preparation/mixture itself. |
| Melting point               | : -39 °C (pour point) (ASTM D 97)                                |
| Freezing point              | : Not available  |
| Boiling point               | : Not available  |
| Flammability                | : Not applicable   |
| Explosive properties        | : None (according to composition).                               |
| Oxidising properties        | : None (according to composition).                               |
| Explosive limits            | : ≥ 45 g/m <sup>3</sup> (Aerosol)                                |
| Lower explosive limit (LEL) | : Not available  |
| Upper explosive limit (UEL) | : Not available  |
| Flash point                 | : 210 °C (ASTM D 92)   |
| Auto-ignition temperature   | : Not available  |
| Decomposition temperature   | : Not available  |
| pH                          | : Not applicable   |
| Viscosity, kinematic        | : 55 mm <sup>2</sup> /s (40 °C) (ASTM D 445)                     |
| Solubility                  | : Water: Immiscible and insoluble                                |
| Log Kow                     | : Not applicable for mixtures                                    |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                                  |  |
|----------------------------------|--|
| Log Pow                          | : Not applicable for mixtures                                  |
| Vapour pressure                  | : < 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010) |
| Vapour pressure at 50 °C         | : Not available  |
| Density                          | : 880 kg/m <sup>3</sup> (15 °C) (ASTM D 1298)                  |
| Relative density                 | : Not available  |
| Relative vapour density at 20 °C | : > 1 (according to composition)                               |
| Particle size                    | : Not applicable   |
| Particle size distribution       | : Not applicable   |
| Particle shape                   | : Not applicable   |
| Particle aspect ratio            | : Not applicable   |
| Particle aggregation state       | : Not applicable   |
| Particle agglomeration state     | : Not applicable   |
| Particle specific surface area   | : Not applicable   |
| Particle dustiness               | : Not applicable   |

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

|  |                     |
|--|---------------------|
| Relative evaporation rate (butylacetate=1) | : Negligible.       |
| Additional information                     | : No data available |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

### 10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidants.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H<sub>2</sub>S. See also Section 16, "Other information".

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

|                             |   |
|-----------------------------|---|
| Acute toxicity (oral)       | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (dermal)     | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (inhalation) | : Not classified (Based on available data, the classification criteria are not met) |
| Additional information      | : (according to composition)  |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

|                       |                              |
|-----------------------|------------------------------|
| LD50 oral rat         | > 5000 mg/kg bodyweight      |
| LD50 dermal rat       | > 5000 mg/kg bodyweight      |
| LD50 dermal rabbit    | 2000 – 5000 mg/kg bodyweight |
| LC50 Inhalation - Rat | > 5 mg/l/4h                  |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                       |   |
|-----------------------|---|
| LD50 oral rat         | > 5000 mg/kg (API 1982, UBTL 1983 - OECD 401)                       |
| LD50 dermal rabbit    | 2000 – 5000 mg/kg bodyweight (API 1982, UBTL 1984 - OECD 402)       |
| LC50 Inhalation - Rat | 3,9 – 5,3 mg/l/4h (Bio-Research Laboratories, Ltd. 1984 - OECD 403) |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

|                       |   |
|-----------------------|---|
| LD50 oral rat         | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LD50 dermal rabbit    | 2000 – 5000 mg/kg bodyweight (API 1982, UBTL 1984 - OECD 402)   |
| LC50 Inhalation - Rat | 3,9 – 5,3 mg/l/4h (Bio-Research Laboratories, Ltd. 1984 - OECD 403)   |

### Mineral base oil, severely refined (N/A)

|                       |                                    |
|-----------------------|------------------------------------|
| LD50 oral rat         | ≥ 5000 mg/kg bodyweight (OECD 401) |
| LD50 dermal rat       | ≥ 5000 mg/kg bodyweight (OECD 402) |
| LC50 Inhalation - Rat | ≥ 5 mg/l/4h (OECD 403)             |

### Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

|                    |                       |
|--------------------|-----------------------|
| LD50 oral rat      | 3100 mg/kg bodyweight |
| LD50 dermal rabbit | 5000 mg/kg bodyweight |

### Triphenyl phosphite (101-02-0)

|                       |                              |
|-----------------------|------------------------------|
| LD50 oral rat         | 1590 – 3620 mg/kg bodyweight |
| LD50 dermal rat       | 5000 mg/kg bodyweight        |
| LC50 Inhalation - Rat | 6,7 mg/l/4h (1h)             |

|                                   |  |
|-----------------------------------|--|
| Skin corrosion/irritation         | : Not classified (Based on available data, the classification criteria are not met)<br>pH: Not applicable  |
| Additional information            | : (according to composition)<br>This product contains components with a Specific Concentration Limit (SCL).  |
| Serious eye damage/irritation     | : Not classified (Based on available data, the classification criteria are not met)<br>pH: Not applicable  |
| Additional information            | : (according to composition)<br>This product contains components with a Specific Concentration Limit (SCL).  |
| Respiratory or skin sensitisation | : Not classified (Based on available data, the classification criteria are not met)  |
| Additional information            | : (according to composition)<br>Contains 2-tetradecyloxirane, reaction products with boric acid, Triphenyl phosphite.<br>Exposure may produce an allergic reaction |
| Germ cell mutagenicity            | : Not classified (Based on available data, the classification criteria are not met)  |
| Additional information            | : (according to composition)   |
| Carcinogenicity                   | : Not classified (Based on available data, the classification criteria are not met)  |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                        |  |
|------------------------|--|
| Additional information | : (according to composition)<br>This product contains : Lubricating oils (petroleum), C24-50, solvent-extd, dewaxed, hydrogenated; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by solvent extraction and hydrogenation of atmospheric distillation residues. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C24 through C50 and produces a finished oil with a viscosity in the order of 16cSt to 75cSt at 40 °C (104 °F).], Distillates (petroleum), hydrotreated light naphthenic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.<br>All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)<br>No carcinogenic effect |
| Reproductive toxicity  | : Not classified (Based on available data, the classification criteria are not met)  |
| Additional information | : (according to composition)<br>This product contains : O,O,O-tris(2(or 4)-C9-10-isoalkylphenyl) phosphorothioate, toluene, Suspected of damaging fertility. Suspected of damaging the unborn child.   |
| STOT-single exposure   | : Not classified (Based on available data, the classification criteria are not met)  |
| Additional information | : (according to composition)   |

### toluene (108-88-3)

|                      |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

|                        |   |
|------------------------|---|
| STOT-repeated exposure | : Not classified (Based on available data, the classification criteria are not met)   |
| Additional information | : (according to composition)<br>Prolonged exposure for long periods to toluene may also cause damages to the auditory nerves (ototoxicity). These effects are shown at level 10-20 times the exposure limits. |

### Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

|  |                                |
|--|--------------------------------|
| LOAEL (oral, rat, 90 days)               | 125 mg/kg bodyweight/day       |
| NOAEL (dermal, rat/rabbit, 90 days)      | 30 – 2000 mg/kg bodyweight/day |
| NOAEC (inhalation, rat, vapour, 90 days) | 980 mg/m <sup>3</sup>          |

### toluene (108-88-3)

|                        |  |
|------------------------|--|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
|------------------------|--|

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|  |  |
|--|--|
| LOAEL (oral, rat, 90 days)               | 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)   |
| LOAEL (dermal, rat/rabbit, 90 days)      | 100 mg/kg bodyweight/day   |
| NOAEL (oral, rat, 90 days)               | < 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)   |
| NOAEL (dermal, rat/rabbit, 90 days)      | 1000 – 2000 mg/kg bodyweight/day (API 1982, Mobil Environmental and Health Science Laboratory 1983 - OECD 410) |
| NOAEC (inhalation, rat, vapour, 90 days) | 220 – 980 mg/m <sup>3</sup> (Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)    |



# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

|  |   |
|--|---|
| LOAEL (oral, rat, 90 days)               | 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| LOAEL (dermal, rat/rabbit, 90 days)      | 100 mg/kg bodyweight/day  |
| NOAEL (oral, rat, 90 days)               | < 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)  |
| NOAEL (dermal, rat/rabbit, 90 days)      | ≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)                  |
| NOAEC (inhalation, rat, vapour, 90 days) | 220 – 980 mg/m <sup>3</sup> (Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)                             |

### Mineral base oil, severely refined (N/A)

|                            |  |
|----------------------------|--|
| LOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight/day (OECD TG 408) |
|----------------------------|--|

### Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

|                            |                          |
|----------------------------|--------------------------|
| NOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight/day |
|----------------------------|--------------------------|

### Triphenyl phosphite (101-02-0)

|                            |                              |
|----------------------------|------------------------------|
| NOAEL (oral, rat, 90 days) | 15 – 40 mg/kg bodyweight/day |
|----------------------------|------------------------------|

|                        |  |
|------------------------|--|
| Aspiration hazard      | : Not classified (Based on available data, the classification criteria are not met)                  |
| Additional information | : (according to composition)<br>Viscosity, kinematic: > 20,5 mm <sup>2</sup> /s (40 °C) (ASTM D 445) |

### Eni Multitech JD/F 10W-30

|                      |  |
|----------------------|--|
| Viscosity, kinematic | 55 mm <sup>2</sup> /s (40 °C) (ASTM D 445) |
|----------------------|--|

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

### 11.2.2 Other information

|   |  |
|---|--|
| Potential adverse human health effects and symptoms | : Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May produce an allergic reaction |
| Other information                                   | : None   |

## SECTION 12: Ecological information

### 12.1. Toxicity

|  |   |
|--|---|
| Ecology - general  | : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. An uncontrolled release to the environment may produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. Notify authorities if product enters sewers or public waters. |
| Ecology - air  | : This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.  |
| Ecology - water  | : This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)   |
| Ecology - water  | : Harmful to aquatic life.  |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified (Based on available data, the classification criteria are not met)   |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.  
(chronic)

### Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

|                                |                                  |
|--------------------------------|----------------------------------|
| LC50 fish 1                    | > 100 mg/l (Pimephales promelas) |
| LC50 other aquatic organisms 1 | > 10 g/l (LL50)                  |
| EC50 Daphnia 1                 | > 10 g/l                         |
| NOEC chronic fish              | > 5000 mg/l (7d)                 |
| NOEC chronic crustacea         | > 1000 mg/l (21d)                |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                        |   |
|------------------------|---|
| LC50 fish 1            | > 100 mg/l (LL 50, Exxon 1995 - OECD 203)                                       |
| EC50 Daphnia 1         | > 10000 mg/l (EL50, Shell 1988 - OECD 202)                                      |
| NOEC (acute)           | ≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008) |
| NOEC chronic fish      | ≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)    |
| NOEC chronic crustacea | ≥ 1000 mg/l (21d, OECD 211 - Shell 1994)  |
| NOEC chronic algae     | ≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h)                               |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                        |   |
|------------------------|---|
| LC50 fish 1            | > 100 mg/l (LL 50, Exxon 1995 - OECD 203)                                       |
| EC50 Daphnia 1         | > 10000 mg/l (EL50, Shell 1988 - OECD 202)                                      |
| NOEC (acute)           | ≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008) |
| NOEC chronic fish      | ≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)    |
| NOEC chronic crustacea | ≥ 1000 mg/l (21d, OECD 211 - Shell 1994)  |
| NOEC chronic algae     | ≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h)                               |

### 2-tetradecyloxirane, reaction products with boric acid

|                      |                                       |
|----------------------|---------------------------------------|
| LC50 fish 1          | > 100 mg/l                            |
| EC50 Daphnia 1       | > 100 mg/l (Daphnia magna, 2 d)       |
| EC50 Daphnia 2       | 20 mg/l (Daphnia magna, 21 d)         |
| EC50 72h - Algae [1] | > 100 mg/l (Selenastrum capricomutum) |

### Mineral base oil, severely refined (N/A)

|                |                                   |
|----------------|-----------------------------------|
| LC50 fish 1    | > 100 mg/l (LL 50)                |
| EC50 Daphnia 1 | > 10000 mg/l WAF, 48 h (OECD 202) |

### Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

|                        |                       |
|------------------------|-----------------------|
| LC50 fish 1            | 46 mg/l               |
| EC50 Daphnia 1         | 75 mg/l (OECD 202)    |
| EC50 72h - Algae [1]   | 240 – 410 mg/l (EL50) |
| NOEC chronic crustacea | 0,4 mg/l              |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Triphenyl phosphite (101-02-0)

|                |               |
|----------------|---------------|
| LC50 fish 1    | 12 – 100 mg/l |
| EC50 Daphnia 1 | 0,94 mg/l     |

### 12.2. Persistence and degradability

#### Eni Multitech JD/F 10W-30

|                               |  |
|-------------------------------|--|
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
|-------------------------------|--|

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                               |  |
|-------------------------------|--|
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Biodegradation                | 31 % (28d, Exxon 1995)   |

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                               |  |
|-------------------------------|--|
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Biodegradation                | 31 % (28d, Exxon 1995)   |

#### 2-tetradecyloxirane, reaction products with boric acid

|                               |                            |
|-------------------------------|----------------------------|
| Persistence and degradability | Not readily biodegradable. |
| Biodegradation                | 17,3 % 28 d                |

#### Mineral base oil, severely refined (N/A)

|                               |  |
|-------------------------------|--|
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
|-------------------------------|--|

#### Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

|                |                        |
|----------------|------------------------|
| Biodegradation | 5 % (28d) (OECD 301 D) |
|----------------|------------------------|

### Triphenyl phosphite (101-02-0)

|                |                                |
|----------------|--------------------------------|
| Biodegradation | 0,1 – 0,9 % (28d) (OECD 301 D) |
|----------------|--------------------------------|

### 12.3. Bioaccumulative potential

#### Eni Multitech JD/F 10W-30

|                           |                             |
|---------------------------|-----------------------------|
| Log Pow                   | Not applicable for mixtures |
| Log Kow                   | Not applicable for mixtures |
| Bioaccumulative potential | Not established.            |

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|            |                   |
|------------|-------------------|
| BCF fish 1 | 0,4 – 6280 l/kg   |
| BCF fish 2 | 3,16 – 71100 l/kg |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|                           |   |
|---------------------------|---|
| Log Pow                   | 1,99 – 18,02  |
| Log Kow                   | Not applicable (UVCB)   |
| Bioaccumulative potential | The test methods for this endpoint are not applicable to UVCB substances. |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                           |   |
|---------------------------|---|
| BCF fish 1                | 0,4 – 6280 l/kg   |
| BCF fish 2                | 3,16 – 71100 l/kg   |
| Log Pow                   | 1,99 – 18,02  |
| Log Kow                   | Not applicable (UVCB)   |
| Bioaccumulative potential | The test methods for this endpoint are not applicable to UVCB substances. |

### 2-tetradecyloxirane, reaction products with boric acid

|         |     |
|---------|-----|
| Log Kow | 9,4 |
|---------|-----|

### Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)

|         |   |
|---------|---|
| Log Kow | 3,6 (Octanol Water Coefficient test - 0,1 days) |
|---------|---|

### Triphenyl phosphite (101-02-0)

|         |      |
|---------|------|
| Log Kow | 6,62 |
|---------|------|

## 12.4. Mobility in soil

### Eni Multitech JD/F 10W-30

|                |                    |
|----------------|--------------------|
| Ecology - soil | No data available. |
|----------------|--------------------|

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                |   |
|----------------|---|
| Log Koc        | 1,71 – 14,7   |
| Ecology - soil | The test methods for this endpoint are not applicable to UVCB substances. |

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

|                |   |
|----------------|---|
| Log Koc        | 1,71 – 14,7   |
| Ecology - soil | The test methods for this endpoint are not applicable to UVCB substances. |

## 12.5. Results of PBT and vPvB assessment

### Eni Multitech JD/F 10W-30

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

|                                |   |
|--------------------------------|---|
| Results of PBT-vPvB assessment | The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
|--------------------------------|---|

### Component

|  |  |
|--|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
|--|--|

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|  |  |
|--|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)    | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Mineral base oil, severely refined (N/A)                               | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII<br>This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)       | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII<br>This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII  |

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Other adverse effects : None  
Additional information : This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.  
Sewage disposal recommendations : Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.  
Product/Packaging disposal recommendations : European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05\* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.  
Additional information : Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.  
Ecology - waste materials : The product as it is does not contain halogenated substances.  
EURAL code (EWC) : 13 02 05\* - Mineral-based non-chlorinated engine, gear and lubricating oils

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR                                  | IMDG           | IATA           | ADN            | RID            |
|--------------------------------------|----------------|----------------|----------------|----------------|
| <b>14.1. UN number or ID number</b>  |                |                |                |                |
| Not applicable                       | Not applicable | Not applicable | Not applicable | Not applicable |
| <b>14.2. UN proper shipping name</b> |                |                |                |                |
| Not applicable                       | Not applicable | Not applicable | Not applicable | Not applicable |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 14.3. Transport hazard class(es)

|                |                |                |                |                |
|----------------|----------------|----------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
|----------------|----------------|----------------|----------------|----------------|

### 14.4. Packing group

|                |                |                |                |                |
|----------------|----------------|----------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
|----------------|----------------|----------------|----------------|----------------|

### 14.5. Environmental hazards

|                |                |                |                |                |
|----------------|----------------|----------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
|----------------|----------------|----------------|----------------|----------------|

None.

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

| Reference code | Applicable on   | Entry title or description   |
|----------------|---|--|
| 3(a)           | toluene   | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F   |
| 3(b)           | Distillates (petroleum), hydrotreated light naphthenic ; toluene ; Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) ; Triphenyl phosphite | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10  |
| 3(c)           | Eni Multitech JD/F 10W-30 ; Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) ; Triphenyl phosphite  | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1  |
| 40.            | toluene   | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not. |
| 48.            | toluene   | Toluene  |

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### Finland

Finnish National Regulations : Occupational Safety and Health Act No. 738/2002.

#### France

##### Maladies professionnelles (F)

| Code     | Description   |
|----------|---|
| RG 4 BIS | Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them   |
| RG 36    | Diseases caused by oils and fats of mineral or synthetic origin   |
| RG 84    | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

#### Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

Water hazard class (WGK) (D) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

National Rules and Recommendations : TRGS 400: Hazard assessment for activities involving Hazardous Substances  
TRGS 401: Risks resulting from skin contact - identification, assessment, measures  
TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure  
TRGS 555: Working instruction and information for workers  
TRGS 800: Fire protection measures  
TRGS 900: Occupational Exposure Limits

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

VbF class (D) : Not applicable.

#### Netherlands

Waterbezuwaarlijkheid : 8 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

9 - Harmful to aquatic organisms

Saneringsinspanningen : C - Minimize discharge

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|  |   |
|--|---|
| SZW-lijst van kankerverwekkende stoffen              | : None of the components are listed   |
| SZW-lijst van mutagene stoffen                       | : Distillates (petroleum), hydrotreated light naphthenic, Distillates (petroleum), solvent-dewaxed heavy paraffinic, Distillates (petroleum), solvent-dewaxed heavy paraffinic are listed |
| SZW-lijst van reprotoxische stoffen – Borstvoeding   | : None of the components are listed   |
| SZW-lijst van reprotoxische stoffen – Vruchtbaarheid | : None of the components are listed   |
| SZW-lijst van reprotoxische stoffen – Ontwikkeling   | : toluene is listed   |
| <b>Denmark</b>                                       |   |
| Danish National Regulations                          | : Young people under 18 years are not allowed to use the product<br>Pregnant/breastfeeding women working with the product must not be in direct contact with it                           |
| <b>Norway</b>  |   |
| Norwegian National Regulations                       | : Working Environment Act (LOV-2005-06-17 NO. 62).  |
| <b>Sweden</b>  |   |
| Swedish National Regulations                         | : Work Environment Act (1977: 1160).<br>Chemical Hazards in the Working Environment (AFS 2011:19).<br>This product is in compliance with Ordinance 1998:944.                              |
| <b>Switzerland</b>                                   |   |
| Storage class (LK)                                   | : LK 10/12 - Liquids  |

### 15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been not carried out

## SECTION 16: Other information

| Indication of changes: |  |          |       |
|------------------------|--|----------|-------|
| Section                | Changed item                           | Change   | Notes |
|                        | Revision date                          | Modified |       |
|                        | Comments                               | Modified |       |
|                        | Supersedes                             | Modified |       |
|                        | Date of issue                          | Modified |       |
| 1.1                    | Formula                                | Modified |       |
| 3                      | Composition/information on ingredients | Modified |       |

| Abbreviations and acronyms: |   |
|-----------------------------|---|
|                             | Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product. |
|                             | N/A = not applicable  |
|                             | N/D = not available   |
| ADN                         | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways   |
| ADR                         | European Agreement concerning the International Carriage of Dangerous Goods by Road   |
| ATE                         | Acute Toxicity Estimate   |
| BCF                         | Bioconcentration factor   |
| CLP                         | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008   |
| DMEL                        | Derived Minimal Effect level  |
| DNEL                        | Derived-No Effect Level   |
| EC50                        | Effective concentration for 50 percent of test population (median effective concentration)  |
| IARC                        | International Agency for Research on Cancer   |



# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|       |  |
|-------|--|
| IATA  | International Air Transport Association  |
| IMDG  | International Maritime Dangerous Goods   |
| LC50  | Lethal concentration for 50 percent of test population (median lethal concentration)               |
| LD50  | Lethal dose for 50 percent of test population (median lethal dose)                                 |
| LOAEL | Lowest Observed Adverse Effect Level   |
| NOAEC | No-Observed Adverse Effect Concentration   |
| NOAEL | No-Observed Adverse Effect Level   |
| NOEC  | No-Observed Effect Concentration   |
| OECD  | Organisation for Economic Co-operation and Development   |
| PBT   | Persistent Bioaccumulative Toxic   |
| PNEC  | Predicted No-Effect Concentration  |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006 |
| RID   | Regulation concerning the International Carriage of Dangerous Goods by Railways                    |
| SDS   | Safety Data Sheet  |
| STP   | Sewage treatment plant   |
| vPvB  | Very Persistent and Very Bioaccumulative   |

|                   |  |
|-------------------|--|
| Data sources      | : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.  |
| Training advice   | : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.   |
| Other information | : Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H <sub>2</sub> S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H <sub>2</sub> S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H <sub>2</sub> S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. |

| Full text of H- and EUH-statements: |   |
|-------------------------------------|---|
| Acute Tox. 4 (Oral)                 | Acute toxicity (oral), Category 4                                 |
| Aquatic Acute 1                     | Hazardous to the aquatic environment – Acute Hazard, Category 1   |
| Aquatic Chronic 1                   | Hazardous to the aquatic environment – Chronic Hazard, Category 1 |
| Aquatic Chronic 2                   | Hazardous to the aquatic environment – Chronic Hazard, Category 2 |
| Asp. Tox. 1                         | Aspiration hazard, Category 1                                     |
| Eye Dam. 1                          | Serious eye damage/eye irritation, Category 1                     |
| Eye Irrit. 2                        | Serious eye damage/eye irritation, Category 2                     |
| Flam. Liq. 2                        | Flammable liquids, Category 2                                     |
| Repr. 2                             | Reproductive toxicity, Category 2                                 |
| Skin Irrit. 2                       | Skin corrosion/irritation, Category 2                             |
| Skin Sens. 1                        | Skin sensitisation, Category 1                                    |

# Eni Multitech JD/F 10W-30

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

|               |   |
|---------------|---|
| Skin Sens. 1B | Skin sensitisation, category 1B   |
| STOT RE 2     | Specific target organ toxicity – Repeated exposure, Category 2  |
| STOT SE 3     | Specific target organ toxicity – Single exposure, Category 3, Narcosis  |
| H225          | Highly flammable liquid and vapour.   |
| H302          | Harmful if swallowed.   |
| H304          | May be fatal if swallowed and enters airways.   |
| H315          | Causes skin irritation.   |
| H317          | May cause an allergic skin reaction.  |
| H318          | Causes serious eye damage.  |
| H319          | Causes serious eye irritation.  |
| H336          | May cause drowsiness or dizziness.  |
| H361d         | Suspected of damaging the unborn child.   |
| H373          | May cause damage to organs through prolonged or repeated exposure.  |
| H400          | Very toxic to aquatic life.   |
| H410          | Very toxic to aquatic life with long lasting effects.   |
| H411          | Toxic to aquatic life with long lasting effects.  |
| H412          | Harmful to aquatic life with long lasting effects.  |
| EUH208        | Contains 2-tetradecyloxirane, reaction products with boric acid, Triphenyl phosphite. May produce an allergic reaction. |

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

|                   |      |                    |
|-------------------|------|--------------------|
| Aquatic Chronic 3 | H412 | Calculation method |
|-------------------|------|--------------------|

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.